




■ 图示(Pic. shown) : TL039T-04P-G12


General. PCB Connector Rated : 320V,10A
Single row , 3.5mm pitch , 02 ~ 24 Pole
Wiring orientation: 90°(wire to plug-in)
Spring clamp unit.

认证 (Approval) :



■ 技术参数Technical Data		UL standard			IEC standard		
UL应用组别(UL Application group)		UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)		150V	--	--	160V	160V	320V
额定电流(Rated current)		7A	--	--	10A	10A	10A
额定连接容量(Rated connection capacity)		28 ~ 16AWG			0.5 ~ 1.5mm ²		
刚性导线横截面 (AWG) (Conductor cross section,solid)					28~16		
柔性导线横截面 (AWG) (Conductor cross section,stranded)					28~16		
刚性导线横截面 (mm2) (Conductor cross section,rigid)					0.5~1.5		
柔性导线横截面 (mm2) (Conductor cross section,flexible)					0.5~1.5		
柔性导线横截面, 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic sleeve)					0.5~1.0		
柔性导线横截面, 带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)					0.5		
2根具有相同横截面的导线, 柔性, 带TWIN套管及塑料套管(mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)					--		
绝缘材料(Insulation Material)					PA66 UL94 V-0		
绝缘材料组别(Material group)					I		
电流承载部件材料和镀层(Material & Plating of Current carrier)					Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)					Stainless		
耐电压(1分钟)(Withstanding Voltage/1Min)					1300V		
额定冲击电压(Rated surge voltage)					2500V		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)					/		
固定螺丝(Mounting Screw) , 扭矩(torque)					--		
剥线长度(Wire stripping length)					7mm		
使用温度(Operating temperature)					-40°C up to +115°C		
存储温度(Storage temperature)					-40°C up to +70°C		
存储相对湿度(Storage relative humidity)					≤70%		
焊接方式(Soldering recommend)					--		

■ 订购方式(How to order)



针座 (Pin header) — single row

P/N : TL006P

Wiring orientation :

90° (plug-in to board)

Rated : 250V,12A