


PCB terminal block — TL series(Raising Clamp)—TL306R



■ 图示(Pic. shown) : TL306R-05P-G12S(M3)


PCB terminal block Rated :320V,24A , 2.5mm²

Single row , 5.08mm pitch , 02P-24P Pole

Wiring orientation: 90°(wire-to-board)


Screw clamp unit: M3, 0.4Nm(02P), 0.5Nm($\geq$ 03P)

认证 (Approval) :



■ 技术参数Technical Data		UL standard			IEC standard		
UL应用组别(UL Application group)		UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)		300V	--	300V	--	320V	--
额定电流(Rated current)		20A	--	10A	--	24A	--
额定连接容量(Rated connection capacity)		24~12AWG			0.2mm ² ~2.5mm ² ,4.0mm ² Sol		
刚性导线横截面 (AWG) (Conductor cross section,solid)				24~12			
柔性导线横截面 (AWG) (Conductor cross section,stranded)				24~12			
刚性导线横截面 (mm2) (Conductor cross section,rigid)				0.2~4.0			
柔性导线横截面 (mm2) (Conductor cross section,flexible)				0.2~2.5			
柔性导线横截面 , 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic				0.25~2.5			
柔性导线横截面 , 带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)				0.25~2.5			
2根具有相同横截面的导线 , 柔性 , 带TWIN套管及塑料套管(mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)				0.5~1.5			
绝缘材料(Insulation Material)				PA66 UL94 V-0			
绝缘材料组别(Material group)				I			
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated			
接线弹片材料(Material of Clamp spring)				--			
耐电压(1分钟)(Withstanding Voltage/1Min)				2000V			
额定冲击电压(Rated surge voltage)				4KV			
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M3 , 0.4Nm(02P) , 0.5Nm(≥03P)			
固定螺丝(Mounting Screw) , 扭矩(torque)				--			
剥线长度(Wire stripping length)				5.8~6.2mm			
使用温度(Operating temperature)				-40°C up to +105°C(UL)/-40°C up to +120°C(IEC)			
存储温度(Storage temperature)				-40°C up to +70°C			
存储相对湿度(Storage relative humidity)				≤70%			
焊接方式(Soldering recommend)		Wave soldering ,260°C 5S Max (Single Wave) , 260°C 10S Max(Double Wave)					

订购方式(How to order)



Web: www.tielee.com

TEL:+86-574-6347-9600.6389-6436

Mail : sale@china-tianli.cn

地址:中国浙江省宁波杭州湾新区庵东工业园区纬三路138号

ADD : 138 , Weisan Rd.,Andong Development Zone, Hangzhou Bay Area, Ningbo, Zhejiang, China