


PCB Connector — TLP series (Female Connector)— TLPS-200R



■ 图示(Pic. shown) : TLPS-200R-06P-G12S(M3)

General.

PCB Connector Rated : 320V, 20A , 4mm²
Single row , 5.00mm pitch , 02 ~ 24 Pole
Wiring orientation: 90°(wire to plug-in)
Screw clamp unit: M3, 0.5 ~ 0.7N·m

认证 (Approval) :



技术参数Technical Data		UL standard			IEC standard		
UL应用组别(UL Application group)	IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
		B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)		300V	--	300V	250V	320V	630V
额定电流(Rated current)		16A	--	10A	20A	20A	20A
额定连接容量(Rated connection capacity)		30 ~ 12AWG			0.2 ~ 4mm ²		
刚性导线横截面 (AWG) (Conductor cross section,solid)					30~12		
柔性导线横截面 (AWG) (Conductor cross section,stranded)					30~12		
刚性导线横截面 (mm2) (Conductor cross section,rigid)					0.2~4		
柔性导线横截面 (mm2) (Conductor cross section,flexible)					0.2~4		
柔性导线横截面, 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible, with ferrule without plastic sleeve)					0.2~2.5		
柔性导线横截面, 带绝缘套管的冷压头 (mm2) (Conductor cross section flexible, with ferrule with plastic sleeve)					0.2~2.5		
2根具有相同横截面的导线, 柔性, 带TWIN套管及塑料套管 (mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)					0.5~1.5		
绝缘材料(Insulation Material)					PA66 UL94 V-0		
绝缘材料组别(Material group)					I		
电流承载部件材料和镀层(Material & Plating of Current carrier)					Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)					--		
耐电压(1分钟)(Withstanding Voltage/1Min)					1600V		
额定冲击电压(Rated surge voltage)					4000V		
接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.)					M3, 0.5 ~ 0.7N·m		
固定螺丝(Mounting Screw), 扭矩(torque)					--		
剥线长度(Wire stripping length)					6.5 ~ 7.5mm		
使用温度(Operating temperature)					-40°C up to +115°C(UL)/-40°C up to +120°C(IEC)		
存储温度(Storage temperature)					-40°C up to +70°C		
存储相对湿度(Storage relative humidity)					≤70%		
焊接方式(Soldering recommend)					--		

■ 订购方式(How to order)

TLPS	2	00	R	XXXX	XXP	X	X	(M3)
Series No. 系列号	Pitch间距 2=5.00mm	Differentiate Number 区分号	Connection angle 角度 R=90° wire to plug-in	Special code 特编号 XXXX=custom-made blank=standard	No. of Poles 极数 02 ~ 24P	Color 颜色 Green : G12	Screw Type 螺丝S=Slot C=Cross	Screw Type

■ 编码片 Coding key



P/N:
TLPCK-002-S

■ 针座 (Pin header) — single row




P/N : TLPH-200V
Orientation :
90° (plug-in to board)
Rated:630V,20A
Open side(stack available)



P/N : TLPHC-200V
Orientation :
90° (plug-in to board)
Rated:630V,20A
Closed side

■ 针座 (Pin header) — single row



P/N : TLPH-200R
Orientation :
180° (plug-in to board)
Rated:630V,20A
Open side(stack available)



P/N : TLPHC-200R
Orientation :
180° (plug-in to board)
Rated:630V,20A
Closed side

■ 针座 (Pin header) — single row



P/N : TLPH-200R-1603
Orientation :
180° (plug-in to board)
Rated:630V,20A
Open side(stack available)



P/N : TLPHC-200R-1603
Orientation :
180° (plug-in to board)
Rated:630V,20A
Closed side

■ 针座 (Pin header) — single row



P/N : TLPH-200V-XXP-HT
Orientation :
90° (plug-in to board)
Rated:630V,20A
Open side(stack available)



P/N : TLPHC-200V-XXP-HT
Orientation :
90° (plug-in to board)
Rated:630V,20A
Closed side

■ 针座 (Pin header) — single row



P/N : TLPH-200R-XXP-HT
Orientation :
180° (plug-in to board)
Rated : 630V,20A
Open side(stack available)



P/N : TLPHC-200R-XXP-HT
Orientation :
180° (plug-in to board)
Rated:630V,20A
Closed side

■ 针座 (Pin header) — dual row in 1 plane




P/N : TLPHDC-200V
Orientation :
90° (plug-in to board)
Rated:320V,20A
Closed side



P/N : TLPHDC-200R
Orientation :
180° (plug-in to board)
Rated : 320V,20A
Closed side

■ 针座 (Pin header) — single row



P/N : TLPH-201R
Orientation :
Right(Fix on PCB)
Rated : 630V,20A
Open side(stack available)



P/N : TLPH-201RL
Orientation :
Left(Fix on PCB)
Rated : 630V,20A
Open side(stack available)

■ 针座 (Pin header) — dual row staggered



P/N : TLPHD-203V
Orientation :
90° (plug-in to board)
Rated : 320V,20A
Open side(stack available)



P/N : TLPHD-203R
Orientation :
180° (plug-in to board)
Rated : 320V,20A
Open side(stack available)

■ 针座 (Pin header) — dual row staggered



P/N : TLPHDC-203V
Orientation :
90° (plug-in to board)
Rated : 320V,20A
Closed side



P/N : TLPHDC-203R
Orientation :
180° (plug-in to board)
Rated : 320V,20A
Closed side