





■ 图示(Pic. shown) : TLPSW-207-04P (G12)

General. PCB Connector Rated : 320V,20A , 2.5mm²
Single row , 5.00mm pitch , 02 ~ 24 Pole
Wiring orientation: 180°(wire to plug-in)
Screw clamp unit: M3.0, 0.6Nm Max

认证 (Approval) :  

■ 技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group) IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	320V	--
额定电流(Rated current)	16A	--	10A	--	20A	--
额定连接容量(Rated connection capacity)	30-12AWG			0.2~2.5mm ² & 4.0mm ² Sol		
刚性导线横截面 (AWG) (Conductor cross section,solid)				30 ~ 12		
柔性导线横截面 (AWG) (Conductor cross section,stranded)				30 ~ 12		
刚性导线横截面 (mm2) (Conductor cross section,rigid)				0.2 ~ 4.0		
柔性导线横截面 (mm2) (Conductor cross section,flexible)				0.2 ~ 2.5		
柔性导线横截面 , 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic				0.25 ~ 1.5		
柔性导线横截面 , 带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)				0.25 ~ 2.5		
2根具有相同横截面的导线 , 柔性 , 带TWIN套管及塑料套管(mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)				0.5 ~ 1.5		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
绝缘材料组别(Material group)				I		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				Stainless steel		
耐电压(1分钟)(Withstanding Voltage/1Min)				2000V		
额定冲击电压(Rated surge voltage)				4000V		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M3.0 , 0.6N.m Max		
固定螺丝(Mounting Screw) , 扭矩(torque)				M2.5 , 0.5N.m		
剥线长度(Wire stripping length)				6.5 ~ 7.5mm		
使用温度(Operating temperature)				-40°C up to +115°C		
存储温度(Storage temperature)				-40°C up to +70°C		
存储相对湿度(Storage relative humidity)				≤70%		
焊接方式(Soldering recommend)				--		

■ 订购方式(How to order)



■ 编码片 Coding key



P/N:
TLPSW-002-S

■ 针座 (Pin header) — single row



P/N : TLPHW-200V
Orientation :
90° (plug-in to board)
Rated:320V,20A
Closed side



P/N : TLPHW-200R
Orientation :
180° (plug-in to board)
Rated:320V,20A
Closed side

■ 针座 (Pin header) — dual row in 1 plane



P/N : TLPHDW-200V
Orientation :
90° (plug-in to board)
Rated:320V,17.5A
Close side



P/N : TLPHDW-200R
Orientation :
180° (plug-in to board)
Rated:320V,17.5A
Close side

■ 针座 (Pin header) — dual row staggered



P/N : TLPHDW-203V
Orientation :
90° (plug-in to board)
Rated:320V,17.5A
Open side(stack available)



P/N : TLPHDW-203R
Orientation :
180° (plug-in to board)
Rated:320V,17.5A
Close side