


Terminal Strip — TLB series — TLB-200H



■ 图示(Pic. shown) : TLB-200H-12P-TS

General. Terminal Strip Rated : 450V,41A , 6mm²
10.0mm pitch , 02-12 Pole
Wire-to-Wire Connection
Screw clamp unit: M3, 0.5Nm Max

认证 (Approval) :



技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	250V	250V	250V	--	450V	--
额定电流(Rated current)	30A	30A	10A	--	41A	--
额定连接容量(Rated connection capacity)	22~10AWG			2.5~6mm ²		
刚性导线横截面 (AWG) (Conductor cross section,solid)	22~10					
柔性导线横截面 (AWG) (Conductor cross section,stranded)	22~12					
刚性导线横截面 (mm2) (Conductor cross section,rigid)	2.5~6					
柔性导线横截面 (mm2) (Conductor cross section,flexible)	2.5~4					
绝缘材料(Insulation Material)	PA66 UL94 V-2					
绝缘材料组别(Material group)	I					
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Ni plated					
接线弹片材料(Material of Clamp spring)	--					
耐电压(1分钟)(Withstanding Voltage/1Min)	1600V					
额定冲击电压(Rated surge voltage)	--					
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)	M3.0 , 0.5N.m Max					
固定螺丝(Mounting Screw) , 扭矩(torque)	--					
剥线长度(Wire stripping length)	5.5-6.5mm					
使用温度(Operating temperature)	-40℃ up to +80℃(UL) /-40℃ up to +100℃(IEC)					
存储温度(Storage temperature)	-40℃ up to +70℃					
存储相对湿度(Storage relative humidity)	≤70%					
焊接方式(Soldering recommend)	--					

■ 订购方式(How to order)

