




■ 图示(Pic. shown) : TLPSW-302R-08P-G12

General.

PCB Connector Rated : 630V,15A , 2.5mm²

Single row , 5.08mm pitch , 02 ~ 24 Pole

Wiring orientation: 90°(wire to plug-in)

Spring clamp unit.

认证 (Approval) :



■ 技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	250V	320V	630V
额定电流(Rated current)	12A	--	10A	15A	15A	15A
额定连接容量(Rated connection capacity)	26 ~ 12AWG			0.2 ~ 2.5mm ²		
刚性导线横截面 (AWG) (Conductor cross section,solid)				26 ~ 12		
柔性导线横截面 (AWG) (Conductor cross section,stranded)				26 ~ 12		
刚性导线横截面 (mm2) (Conductor cross section,rigid)				0.2 ~ 2.5		
柔性导线横截面 (mm2) (Conductor cross section,flexible)				0.2 ~ 2.5		
柔性导线横截面, 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic sleeve)				0.2 ~ 1.5		
柔性导线横截面, 带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)				0.2~1.0		
2根具有相同横截面的导线, 柔性, 带TWIN套管及塑料套管(mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)				--		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
绝缘材料组别(Material group)				I		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				Stainless		
耐电压(1分钟)(Withstanding Voltage/1Min)				1600V		
额定冲击电压(Rated surge voltage)				4000V		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				/		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				9.0 ~ 10.0mm		
使用温度(Operating temperature)				-40°C up to +115°C		
存储温度(Storage temperature)				-40°C up to +70°C		
存储相对湿度(Storage relative humidity)				≤70%		
焊接方式(Soldering recommend)				--		

■ 订购方式(How to order)

TLPSW	3	02	R	XXXX	XXP	X
Series No. 系列号	Pitch间距 3=5.08mm	Differentiate Number 区分号	Connection angle 角度 R=90° plug-in to board	Special code 特编号 XXXX=custom-made blank=standard	No. of Poles 极数 02 ~ 24P	Color 颜色 Green: G12

■ 编码片 Coding key



P/N:
TLPCK-002-S

■ 针座 (Pin header) — single row



P/N : TLPHW-300V
Orientation :
90° (plug-in to board)
Rated:320V,20A



P/N : TLPHW-300R
Orientation :
180° (plug-in to board)
Rated:320V,20A

■ 针座 (Pin header) — dual row in 1 plane



P/N : TLPHDW-300V
Orientation :
90° (plug-in to board)
Rated:320V,20A



P/N : TLPHDW-300R
Orientation :
180° (plug-in to board)
Rated:320V,20A

■ 针座 (Pin header) — dual row staggered



P/N : TLPHDW-303V
Orientation :
90° (plug-in to board)
Rated:320V,20A



P/N : TLPHDW-303R
Orientation :
180° (plug-in to board)
Rated:320V,20A

■ 针座 (Pin header) — single row



P/N : TLPHSW-304
Orientation :
180° (plug-in to board)
Rated:630V,20A



P/N : TLPHW-300A
Orientation :
45° (plug-in to board)
Rated:630V,20A

■ 针座 (Pin header) — single row



P/N : TLPHW-306
Orientation :
90° (plug-in to board)
Rated:630V,18A