



PCB terminal block — TLM series (Screwless Type) — TLM-303



■ 图示(Pic. shown) : TLM-303-06P-M19

General: PCB terminal block Rated :320V,24A 2.5mm²
Single row , 5.08mm pitch , 02 ~ 24 Pole
Wiring orientation:135°(wire-to-board)
Screwless Type

认证 (Approval) : 

■ 技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	320V	320V	--
额定电流(Rated current)	15A	--	10A	24A	24A	--
额定连接容量(Rated connection capacity)	22AWG ~ 12AWG			0.34mm²~2.5mm²		
刚性导线横截面 (AWG) (Conductor cross section,solid)				22 ~ 12		
柔性导线横截面 (AWG) (Conductor cross section,stranded)				22 ~ 12		
刚性导线横截面 (mm2) (Conductor cross section,rigid)				0.34 ~ 2.5		
柔性导线横截面 (mm2) (Conductor cross section,flexible)				0.34 ~ 2.5		
柔性导线横截面 , 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic				0.34 ~ 1.5		
柔性导线横截面 , 带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)				0.34 ~ 1.5		
2根具有相同横截面的导线,柔性,带TWIN套管及塑料套管(mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)				--		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
绝缘材料组别(Material group)				I		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				Stainless Steel (GrNi)		
耐电压(1分钟)(Withstanding Voltage/1Min)				AC1600V		
额定冲击电压(Rated surge voltage)				4KV		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				--		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				5 ~ 6mm		
使用温度(Operating temperature)				-40℃ up to +120℃(IEC)/-40℃ up to +105℃(UL)		
存储温度(Storage temperature)				-40℃ up to +70℃		
存储相对湿度(Storage relative humidity)				≤70%		
焊接方式(Soldering recommend)	Wave soldering ,260℃ 5S Max (Single Wave) , 260℃ 10S Max(Double Wave)					

■ 订购方式(How to order)

TLM	3	03	XXXX	XXP	X
Series No. 系列号	Pitch间距 3=5.08mm	Differentiate Number 区分号	Special code 特编号 XXXX=custom-made blank=standard	No. of Poles 极数 02-24P	Color:颜色 Grey:M19